

# OMG<sup>®</sup> OlyBond500<sup>®</sup>

## PREMIER ADHESIVE FOR LOW SLOPE ROOFING

OlyBond500<sup>®</sup> is the premier insulation adhesive for low-slope roofing applications. It is a fast-acting, two-component, low-rise polyurethane foam adhesive designed to secure most insulation types to a wide selection of common roof decks and materials. OlyBond500 Insulation Adhesives are easy to use, hassle-free and designed to get you off the roof and onto the next job quickly.



OlyBond500 can be used in both new and re-roofing applications, including jobs that require multiple insulation layers. No matter what size job you have, large or small, there's an OlyBond500 adhesive that's right for your next project.

### FEATURES & BENEFITS

- Odor free – excellent for sensitive areas, such as schools, office buildings and hospitals.
  - Reduces re-roof and construction noise.
  - Rapid application.
  - Chemical cure results in fast set-up time
- OlyBond500 Canisters come with six small mixing tips and three extension tubes.
- No thermal bridging caused by fasteners.
  - Extremely high wind-uplift ratings.
  - Easy to ship; non-hazardous.

### APPROVALS

OlyBond500<sup>®</sup> is approved by most roof system manufacturers and is Factory Mutual, Miami Dade, Florida Building Code and Underwriters Laboratories approved.



Florida Building Code

### COMPATIBILITY

#### Roof Decks and Substrates:

- Structural concrete.
- Gypsum.
- Cementitious wood fiber plank.
- Lightweight insulating concrete.
- Steel (22 Ga. [.75 mm] or thicker with approved cross section).
- Plywood (5/8-in. [16 mm] thick min.).
- Smooth surface BUR.
- Smooth and granular surface modified bitumen (properly prepared).
- Existing sprayed in place polyurethane foam.
- Base sheets.
- Most vapor barriers (including asphaltic and fleece-top).

#### Roof Insulation and Cover Board:

- Polyisocyanurate – 4-ft. x 4-ft. (1 m x 1 m) maximum.
- Expanded polystyrene.
- High density wood fiber.
- Hard cover boards.
- Perlite.
- Certain extruded polystyrene.\*

\*For specific applications, call OMG Roofing Products for assistance.



**Over 1.5 billion sq.ft. installed!**



# OlyBond500®

## PACKAGING & COVERAGE

Packaged in 1500 ml cartridge sets, 4 per case. Typical coverage rate is 4–6 squares (40–55 m<sup>2</sup>) per case depending on the substrate and insulation type.

- Regular
- Winter
- Green



## POWER GUN CORDLESS APPLICATOR

- Includes integrated battery charge indicator gauge, and can be charged in 30 minutes, 50% faster!
- Easy to operate.
- New stand-up power gun applicator comes fully assembled and with heavy duty carrying case.
- Includes two (2) 18 volt Lithium I on batteries (LIB) and your choice of 110V or 220V charger.



**The Power Gun Cordless Applicator comes fully assembled with an extra battery and a convenient carrying case!**

## ORDERING INFORMATION

CAT. NO.	DESCRIPTION	WEIGHT LBS (KG)	PKG QTY
OB500SSGUN-SU18V	Power Gun Cordless Applicator	10 (4.54)	Each
OB500SSMIXTIP-10	Static Mix Tips for all SpotShot Applicators	1 (0.45)	10 ea
OB500SS-R	OlyBond500 SpotShot Regular Formula 40°F (4°C) +	19 (8.62)	(4) 1500 ml Cartridges/Box
OB500SS-W65	OlyBond500 SpotShot Winter Formula 0°–65°F (–17°- +18°C)	19 (8.62)	(4) 1500 ml Cartridges/Box
OB500SSGREEN-R	OlyBond500 Green SpotShot Reg Formula 40°F (4°C) +	19 (8.62)	(4) 1500 ml Cartridges/Box

For more information, contact your local OMG sales representative or visit our website at [OMGRoofing.com](http://OMGRoofing.com).

OMG is a leading U.S. supplier of roofing fasteners, roof insulation adhesives, retrofit roof drains, pipe supports, engineered edge metal systems and rooftop productivity tools. Our products are available nationwide through a network of roofing distributors, and supported by our national network of direct factory sales personnel.



### ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA  
800-633-3800 413-789-0252 [OMGROOFING.COM](http://OMGROOFING.COM)

OlyBond500® is a registered trademark of OMG, Inc. Copyright © 2019 OMG, Inc. All rights reserved.

Superior productivity.  
Superior performance.

