



Masonry Anchor

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

The OMG Masonry Anchor is designed to attach termination bar to concrete or masonry walls. This fastener has a zinc plated steel pin and is available in two diameters, 4 and 6 mm (1/4-in. and 3/16-in.). Lengths range from 22 to 50 mm (7/8-in. to 2-in.).

APPLICATION

Predrill a pilot hole. The diameter of the hole must match the shank diameter of the Masonry Anchor. The predrilled hole must be a minimum of 13 mm (1/2-in.) deeper than the anchor embedment. Install the OMG Masonry Anchor with a hammer.


Minimum fastener embedment into the wall should be 16 mm (5/8-in.) for the 4 mm (3/16-in.) shank Masonry Anchor and 20 mm (3/4-in.) for the 6 mm (1/4-in.) shank Masonry Anchor.

SPECIFICATION

The fastener will be an OMG Masonry Anchor with a zinc plated steel pin and shall be 4 or 6 mm (1/4-in. or 3/16-in.) in diameter. Lengths shall be 22, 19, 25, 31, 38, or 50 mm. (7/8-in., 3/4-in., 1-in., 1 1/4-in., 1 1/2-in. or 2-in.).

PLATES & ACCESSORIES

To be used with channel, lip, flat or heavy flat termination bar depending on application.



Use a 4 or 6 mm (1/4-in. or 3/16-in.) carbide tip masonry drill bit.

PACKAGING

All OMG Masonry Anchors are available in 1,000 piece bulk cartons or 1000 piece cartons which contain ten 100 piece boxes.



USE WITH
CMU
M
SC
DECK TYPES

PHYSICAL DATA

The data below is constant for each OMG Masonry Anchor.

DIAMETERS	MATERIAL
4 and 6 mm (3/16" and 1/4")	Zinc Alloy Pin: Zinc Plated Steel

ORDERING INFORMATION

MASONRY ANCHOR

Bulk Cartons

CAT. NO.	PIN DIAMETER MM (IN)	PIN LENGTH MM (IN)	PKG QTY	WEIGHT KG (LBS.)
MA22-4	4 (3/16)	22 (7/8)	1000	4.54 (10)
MA25-6	6 (1/4)	19 (3/4)	1000	6.75 (15)
MA30-6	6 (1/4)	25 (1)	1000	9.08 (20)
MA38-6	6 (1/4)	31 (1 1/4)	1000	9.98 (22)
MA38-6	6 (1/4)	38 (1 1/2)	1000	11.25 (25)
MA450-6	6 (1/4)	50 (2)	1000	13.95 (31)

*All sizes are nominal.

KEY:

S Steel	SC Structural Concrete
W Wood	LC Lightweight Concrete
G Gypsum	LWIC Lightweight Insulating Concrete
P Purlins	CWF Cementitious Wood Fiber



ROOFING PRODUCTS

153 BOWLES ROAD,
AGAWAM, MA 01001 USA
+1 413.789.0252

Superior productivity. Superior performance.

INFOEUROPE@OMGINC.COM

Find Us at: www.omgroof.com/euro-reps

Copyright © 2021 OMG, Inc. All rights reserved.

