



RhinoBond® EPDM Plate

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

OMG RhinoBond® EPDM Plates are designed to secure roof insulation and approved clean EPDM roof membranes♦. Plates are 80 mm (3-in.) round, specially coated Galvalume, installed with OMG-manufactured fasteners** on steel, wood or structural concrete roof decks.

All RhinoBond plates have a recessed center and a raised flat bonding surface, and come in easy to handle weather-resistant packaging.

RhinoBond Plates for approved clean EPDM membranes are white.

FEATURES & BENEFITS

- RhinoBond EPDM plates meet ETAG 006 criteria for corrosion resistance. EPDM plates feature a wide welding surface to promote a strong bond.
- RhinoBond Plates are packaged in weather-resistant pails for easy handling.
- Keep lids closed to protect plates from U.V. sun exposure.

APPLICATION

RhinoBond is a proprietary roof attachment system approved for use by select roofing manufacturers. The system requires the use of RhinoBond Plates and OMG manufactured fasteners, as well as a RhinoBond induction tool.

Insulation Types and Thicknesses:

RhinoBond is compatible with most common insulation types, including mineral wool, polyisocyanurate (PIR), DensDeck® and Securock® as well as any insulation that will not melt by the induction welding process. Induction

welding over extruded polystyrene (XPS) or EPS requires a cover board (13 mm (.5-in.) minimum), or the use of the OMG 102 mm Cardboard Disks.

Metal Deck: When using RhinoBond over a metal deck, a minimum of 38 mm (1.5-in.) of insulation over the metal deck is required for proper tool operation.

These recommendations address various technical operating requirements of the RhinoBond Induction Tool only, and are not provided in lieu of any applicable building code or roofing system manufacturer requirements or specifications.

Pull tests should always be conducted to determine proper fastener selection.

PACKAGING

RhinoBond Plates are packaged in plastic weather-resistant pails of 500 pieces each.

ATTENTION: RhinoBond Plates must be protected from prolonged UV (ultra violet) sun exposure. Keep RhinoBond buckets covered when not retrieving plates. Installed RhinoBond plates must be covered with membrane by the end of each workday.

APPROVALS



♦Clean EPDM membrane – currently there are a limited number of clean EPDM options available only in Europe and approved for use with RhinoBond. Always verify membrane suitability and approvals with membrane supplier. RhinoBond is not suitable for use with other EPDM membrane.

**Consult roofing manufacturer for specific system ratings and requirements.



USE WITH
S
W
SC
P
DECK TYPES

PHYSICAL DATA *

The data below is constant for each OMG RhinoBond Plate.

SIZE	MATERIAL
80 mm (3") round	Coated Galvalume

ORDERING INFORMATION

CAT. NO.	MEMBRANE	PKG QTY	WEIGHT KG (LBS)
RBP80A-EPDM	♦EPDM	500	16 (35)

* All Dimensions are nominal.



KEY:

S Steel	SC Structural Concrete
W Wood	LC Lightweight Concrete
G Gypsum	LWIC Lightweight Insulating Concrete
P Purlins	CWF Cementitious Wood Fiber



ROOFING PRODUCTS

153 BOWLES ROAD,
AGAWAM, MA 01001 USA
+1 413.789.0252

INFOEUROPE@OLYFAST.COM
WWW.OMGROOFING.COM

RhinoBond® is a registered trademark of OMG, Inc.
Copyright © 2018 OMG, Inc. All rights reserved.

Superior productivity. Superior performance.

Europe Market Manager:
Lennard Spirig
LSpirig@olyfast.com
Mob: +41 79 200 19 30
Office: +41 71 599 19 30

Benelux:
Ruud Veldwijk
RVeldwijk@olyfast.com
Mob: +31 6 28376030

United Kingdom:
Mick Steeples
MSteeple@olyfast.com
Mob: +44 7824 364850

