



Lite-Deck Plate

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

OMG Lite Deck Plates are made of Galvalume® coated steel. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. These plates are designed to be used with OMG Lite-Deck Fasteners.

APPLICATION

3-in. (75 mm) Lite-Deck Plates are used to secure insulation in lightweight concrete, cementitious wood fiber and gypsum roof decks. Use with OMG Lite-Deck Fasteners.

Lite-Deck Batten Bar is used to secure membrane*. Bar is 18 Ga. (1.3 mm Ga.), and available with 6- or 12-inch (150 or 300 mm) on center hole spacing, and comes in 10-ft. (3.05 m) lengths, 50 pieces/tube.

COATING

OMG Lite-Deck Plates are coated with AZ55 corrosion resistant coating which passes the corrosion requirements of FM Approval Standard 4470 and EAD030351-00-0402.

APPROVALS

*The Lite-Deck fastener is only FM approved for use with Lite-Deck insulation plates for fully adhered and insulation securement applications. FM does not approve mechanically attached systems into Tectum or Gypsum. Always consult with roof system manufacturer for the latest approval ratings.



Factory Mutual listings refer to this product as Lite-Deck Plate.

ORDERING INFORMATION

CAT. NO.	SIZE IN (MM)	PKG QTY	WEIGHT LBS (KG)
TCP03	3 (75)	500	19 (8.62)
BAT18-6LD	6 (150) oc	50	80 (36.32)

3-in. (75 mm)
Galvalume
Lite-Deck Plate



18 Ga. (1.3 mm)
Lite-Deck Bar



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA
800-633-3800 413-789-0252 OMGROOFING.COM

Copyright © 2021 OMG, Inc. All rights reserved.

Superior productivity.
Superior performance.

